

1. Product Description

StenCure® WHITE is a ready-to-use, paraffin-based curing compound that prevents water loss in fresh concrete. Meets the requirements of ASTM C 309 Type II Class A and TS 10966 B-2.

2. Uses

StenCure® WHITE forms a protective layer on fresh concrete surface and prevents water loss. It reflects sunlight, preventing surface heating and reducing water loss. It prevents strength loss and shrinkage cracks that may be caused by premature drying.

The curing material sprayed on the concrete surface makes it unnecessary to take any other precaution (watering or laying wet straw mat, wet sand and plastic sheeting) for the same purpose. Due to these properties, **StenCure® WHITE** is used on all types of large concrete surfaces exposed to external conditions, and especially: airports, runways, aprons and parking areas, concrete access roads, bridges, dams and irrigation canals, prestressed beams, concrete slabs and similar places. After removal from the cured surface, it does not negatively affect the adhesion of road marking paints.

It is suitable for use in interior and exterior applications.

3. Application

StenCure® WHITE is supplied ready to use. After the fresh concrete surface becomes matte (approximately 1 to 2 hours after the application depending on the ambient temperature), it is sprayed on the concrete surface as a thin layer. Spraying can be carried out with a spray gun.

Concrete surfaces must be protected from rain for three hours after application of **StenCure® WHITE**. Consumption is 200-300 g/m² depending on wind, humidity and heat.

4. Cleaning

Application equipment can be cleaned with hot water after work is completed.

5. Safety

Applicators and supervisors must read the Material Safety Data Sheet (SDS) carefully and follow the instructions provided. Emptied packages must be handled in compliance with relevant regulations and laws. The application must be carried out by skilled workers under supervision of experts and the applicators must use all kinds of protective equipment required for the worksite and the task such as goggles, mask and gloves.

6. Storage

Protect the product from freezing. Products must be stored at +5 °C to +35 °C in closed conditions protected from direct sunlight. Shelf life is 1 year without opening the package.

Frozen material cannot be reused.

Water-Retentive Pigmented Paraffin Emulsion for Concrete

Highlights

- Paraffin-based and white colored
- Prevents cracks that may occur during curing by forming a protective layer on fresh concrete
- Reflects sunlight
- Prevents shrinkage cracks
- Prevents strength loss of the concrete
- Can be used indoors and outdoors
- Easy to use



7. Disclaimer

This document is provided for general information and reflects **Stenkim**[®]'s laboratory data and field experience at the time of publication. **Stenkim**[®] reserves the right to revise this information at any time without notice.

Stenkim[®] warrants that its products conform to the stated specifications on delivery. The buyer is responsible for determining the product's suitability for the intended application and for all conditions of transport, storage, handling, and use. **Stenkim**[®] accepts no liability for results obtained under conditions outside its control. **Stenkim**[®]'s liability under this warranty is limited to replacement of non-conforming product and excludes any consequential or indirect damages.

8. Technical Data

Property	Method	Result
Chemical Composition		Paraffin Emulsion
Color		White
Density	EN ISO 2811-2	1 ± 0.05 g/cm ³
Application Rate		200-300 g/m ²
pH	ISO 4316	8 ± 1
Chloride	EN 480-10	None
Shelf Life		1 year
Packaging		200 kg drums or 1,000 kg IBCs

Stenkim[®] reserves the right to make changes to the values in this table at any time.

