

1. Product Description

StenSolver is a flammable mixture containing aromatic and aliphatic solvents. It has high solvency power and does not mix with water. The StenSolver product family consists of three members: **StenSolver PU** designed for solvent-based polyurethane products, **StenSolver EP** designed for solvent-based epoxy products, and **StenSolver CL** designed for general-purpose cleaning.

For each member's chemical composition and detailed application instructions, refer to the corresponding product datasheet.

2. Uses

StenSolver products are designed for cleaning tools and surfaces contaminated with polymer-, epoxy polymer-, and polyurethane-based materials manufactured by **Stenkim®**. It is used to clean equipment contaminated with these materials before the material hardens. Hardened material residues can be softened by soaking in the solvent; thus, cleaning becomes easier.

It is also used for thinning certain solvent-containing products. For member-specific chemical compatibility, dosage and application instructions, consult the product datasheets of **StenSolver PU**, **StenSolver EP** and **StenSolver CL**.

3. Warnings

- **StenSolver** products are for professional use.
- As it is flammable, smoking must be avoided during use and it must be kept away from open flames and sources of sparks.

In enclosed areas, adequate ventilation must be provided and it must not be inhaled for long periods.

- Users must use protective equipment such as masks, goggles, and gloves and take the necessary safety precautions.
- In case of contact with eyes, rinse with plenty of water and consult a doctor for medical treatment.
- People prone to allergic reactions should not use this product.
- As it is a strong solvent, it may affect some organic materials.
- Opened containers must be closed after work is completed, and empty containers must be disposed of in accordance with regulations.

4. Safety

Applicators and supervisors must read the Material Safety Data Sheet (SDS) carefully and follow the instructions provided. Emptied packages must be handled in compliance with relevant regulations and laws. The application must be carried out by skilled workers under supervision of experts and the applicators must use all kinds of protective equipment required for the worksite and the task such as goggles, mask and gloves.

5. Storage

Packages must not be exposed to direct sunlight. It must be stored away from open flame and sources of ignition. Storage temperature must be between 5 and 30 °C.

Under these conditions, the material will retain its properties until the expiration date in unopened packages. The material is flammable.

Solvent and Thinner



6. Disclaimer

This document is provided for general information and reflects **Stenkim®**'s laboratory data and field experience at the time of publication. **Stenkim®** reserves the right to revise this information at any time without notice.

Stenkim® warrants that its products conform to the stated specifications on delivery. The buyer is responsible for determining the product's suitability for the intended application and for all conditions of transport, storage, handling, and use. **Stenkim®** accepts no liability for results obtained under conditions outside its control. **Stenkim®**'s liability under this warranty is limited to replacement of non-conforming product and excludes any consequential or indirect damages.

